



Profibus PA / Foundation Fieldbus transmitter

6350B

- PROFIBUS PA ver. 3.0
- FOUNDATION Fieldbus ver. ITK 4.6
- Automatic switch between protocols
- FISCO-certified
- Basic or LAS capability with F.F.



Application

- Linearized temperature measurement with RTD or TC sensor.
- Converts analog mA signals into digital values on the bus communication.
- Difference, average or redundancy temperature measurement with RTD or TC sensor.
- Linear resistance, potentiometer and bipolar mV measurement.


Technical characteristics

- Bus transmitter with both PROFIBUS PA and FOUNDATION™ Fieldbus communication. A unique switch function ensures automatic shift between the two protocols.
- Set-up for PROFIBUS PA can be done via Siemens Simatic® PDM®, ABB Melody / Harmony and Metso DNA software and for FOUNDATION Fieldbus via Emerson DeltaV, Yokogawa CS 1000 / CS 3000, ABB Melody / Harmony and Honeywell Experion software.
- Built-in simulation mode function.
- Polarity-independent bus connection.
- 24 bit A/D converter ensures high resolution.
- PROFIBUS PA function blocks: 2 analog.
- FOUNDATION Fieldbus function blocks: 2 analog and 1 PID.
- FOUNDATION Fieldbus capability: Basic or LAS.

Mounting / installation

- Mounted vertically or horizontally on a DIN rail. Using the 2-channel version up to 84 channels per meter can be mounted.

Applications



Order:

| Type | Galvanic isolation | Channels |
|-------|--------------------|--------------------------|
| 6350B | 1500 VAC : 2 | Single : A Double : B |

Environmental Conditions

| | |
|------------------------------|----------------------|
| Operating temperature..... | -40°C to +85°C |
| Storage temperature..... | -40°C to +85°C |
| Calibration temperature..... | 20...28°C |
| Relative humidity..... | < 95% RH (non-cond.) |
| Protection degree..... | IP20 |

Mechanical specifications

| | |
|------------------------------|---|
| Dimensions (HxWxD)..... | 109 x 23.5 x 104 mm |
| Weight (1 / 2 channels)..... | 145 / 185 g |
| DIN rail type..... | DIN EN 60715/35 mm |
| Wire size..... | 0.13...2.08 mm ² AWG 26...14 stranded wire |
| Screw terminal torque..... | 0.5 Nm |

Common specifications**Supply**

| | |
|-------------------------------------|--------------|
| Supply voltage..... | 9.0...30 VDC |
| Power dissipation, per channel..... | < 11 mA |

Isolation voltage

| | |
|----------------------|-------------------|
| Test voltage..... | 1.5 kVAC for 60 s |
| Working voltage..... | 50 VRMS / 75 VDC |

Response time

| | |
|-----------------------------------|----------|
| Response time (programmable)..... | 1...60 s |
|-----------------------------------|----------|

| | |
|---------------------------|------------|
| Warm-up time..... | 30 s |
| Signal / noise ratio..... | Min. 60 dB |

| | |
|---------------|-------------------------------------|
| Accuracy..... | Better than 0.05% of selected range |
|---------------|-------------------------------------|

| | |
|-------------------------------------|----------|
| Updating time..... | < 400 ms |
| Execution time, PID controller..... | < 200 ms |

| | |
|-----------------------------------|---------|
| Execution time, analog input..... | < 50 ms |
| Signal dynamics, input..... | 24 bit |

| | |
|-----------------------------|--------------------|
| EMC immunity influence..... | < ±0.1% of reading |
|-----------------------------|--------------------|

| | |
|--|------------------|
| Extended EMC immunity: NAMUR NE21, A criterion, burst..... | < ±1% of reading |
|--|------------------|

Input specifications**RTD input**

| | |
|---------------|---|
| RTD type..... | Pt125...1000, Ni25...1000, Cu10...1000, lin. R, potentiometer |
|---------------|---|

| | |
|--------------------------------|-------------|
| Cable resistance per wire..... | 50 Ω (max.) |
| Sensor current..... | Nom. 0.2 mA |

| | |
|--|---------------|
| Effect of sensor cable resistance (3-/4-wire)..... | < 0.002 Ω / Ω |
| Sensor error detection..... | Yes |

| | |
|------------------------------|--------|
| Short circuit detection..... | < 15 Ω |
|------------------------------|--------|

Linear resistance input

| | |
|----------------------------------|---------------|
| Linear resistance min...max..... | 0 Ω...10000 Ω |
|----------------------------------|---------------|

Potentiometer input

| | |
|------------------------------|---------------|
| Potentiometer min...max..... | 10 Ω...100 kΩ |
|------------------------------|---------------|

TC input

| | |
|------------------------|--------------------------------------|
| Thermocouple type..... | B, E, J, K, L, N, R, S, T, U, W3, W5 |
|------------------------|--------------------------------------|

| | |
|---------------------------------------|----------|
| Cold junction compensation (CJC)..... | < ±0.5°C |
|---------------------------------------|----------|

| | |
|-----------------------------|-----|
| Sensor error detection..... | Yes |
|-----------------------------|-----|

| | |
|--|------------------|
| Sensor error current: When detecting / else..... | Nom. 2 μA / 0 μA |
|--|------------------|

| | |
|------------------------------|--------|
| Short circuit detection..... | < 3 mV |
|------------------------------|--------|

Bipolar current input

| | |
|---|-------------------|
| Measurement range..... | -100...+100 mA |
| Input resistance..... | 10 Ω + PTC < 20 Ω |
| Cable breakage detection (4...20 mA)..... | < 0.3 mA |

Bipolar mV input

| | |
|------------------------------------|----------------|
| Measurement range..... | -800...+800 mV |
| Min. measurement range (span)..... | 2.5 mV |
| Input resistance..... | 10 MΩ |
| Short circuit detection..... | < 3 mV |

Output specifications**PROFIBUS PA connection**

| | |
|--|-----------------------|
| PROFIBUS PA protocol..... | Profile A&B, ver. 3.0 |
| PROFIBUS PA protocol standard..... | EN 50170 vol. 2 |
| PROFIBUS PA address (at delivery)..... | 126 |
| PROFIBUS PA function blocks..... | 2 analog |

FOUNDATION Fieldbus connection

| | |
|--|--------------------------|
| FOUNDATION Fieldbus protocol..... | FF protocol |
| FOUNDATION Fieldbus protocol standard..... | FF design specifications |
| FOUNDATION Fieldbus version..... | ITK 4.6 |
| FOUNDATION Fieldbus capability..... | Basic or LAS |
| FOUNDATION Fieldbus function blocks..... | 2 analog and 1 PID |

Approvals

| | |
|-------------|-------------------------|
| ATEX..... | KEMA 03ATEX1012 X |
| IECEx..... | DEK 14.0071X |
| FM..... | 3015609 |
| CSA..... | 1418937 |
| EAC Ex..... | RU C-DK.HA65.B.00355/19 |