



# Industrial Dehumidifier

## PRODUCT FEATURE

- CNC processed casing, rigid & durable
- Brand compressor, CFC free refrigerant available
- Washable coarse air filter, easy to maintain
- Top air discharge, duct flange available
- Standard hose drain, pump available
- Smart automatic recover function
- Lack/wrong phase protection(3phase unit)
- Timer On/Off, defrost time/temperature set function
- Class F fan motor, Low/High air speed
- Compressor delay start protection, fan delay stop protection




### Customized available

Duct flange, high temperature, Explosion-proof, pump drain etc.



### Durable fan

Class F motor, low/high speed



### Auto restart function

Restart automatically from sudden power outage



### Adjustable defrost time & temperature

Solve icing problem & prolong lifetime

## TECHNICAL SPECIFICATION

Model	ecoFD-D720L	ecoFD-D960L
Capacity (30°C, RH80%)	720L/Day	960L/Day
Power Source	415V/50Hz/3Ph	415V/50Hz/3Ph
Rated Input Power	15KW	22KW
Rated Input Current	30.0A	44.0A
Water Drain	Hose, Φ20mm	Hose, Φ20mm
Refrigerant	R410a / R407c	R410a / R407c
Air Flow	9000m <sup>3</sup> /h	12000 m <sup>3</sup> /h
E.S.P	>150Pa	>150Pa
Available Ambient Temp	5-38°C	5-38°C
Weight	320kg	463kg
Available Area(H=2.6m)	<800m <sup>2</sup>	<1000m <sup>2</sup>
Measurement(W*D*H)	1430*710*1950mm	
Package Size(W*D*H)	1500*750*2130mm	