



- ▶ Detects Water & Base Liquids
- ▶ Made in Low Smoke Zero Halogen Materials
- ▶ Pre-connected in Standard Lengths

## Description

The TTK Sense Cable FG-ECX detects the presence of conductive liquids at any point along its length. The FG-ECX sense cable can be connected to two kinds of TTK's alarm units: Locating Alarm Unit and Non-locating Alarm Unit. It detects and locates leaks to the nearest metre when connected to the locating alarm unit.

The Sense Cable FG-ECX is available in standard, pre-finished lengths of 3, 7 or 15 metres complete with connectors.

Each FG-ECX sense cable is made with special **Low Smoke Zero Halogen materials**, it emits limited smoke and no halogen when exposed to high sources of heat.

## Features & Benefits

### A RELIABLE SENSE CABLE

The FG-ECX sense cable performs the following functions:

- Rapidly detects the leak of any liquid along the length of the cable.
- Detects and locates leaks to the nearest metre when connected to the locating units FG-ALS8 or FG-ALS4.
- Detects leaks only when connected to the non-locating unit FG-A.
- Detects any break or cut to the cable.

Non-absorbant design can be reset in seconds after removal of the leak.

Manufactured with the low smoke zero halogen (LSZH or LS0H) materials, FG-ECX cable emits, when burned, a less optically dense smoke that releases at a lower rate than a non-LSZH cable.

### A MODULAR SYSTEM

The FG-ECX sense cable ensures permanent protection in areas at

risk. FG-ECX is installed to provide the best possible protection in order to cover risks and limit the financial consequences of an undetected leak.

### EASY INSTALLATION

The male and female connectors at the end of each length of FG-ECX cable give quick and dependable connection. Fixing clips are used to fasten the sensing cables in the chosen areas.

### A TOUGH AND STURDY DESIGN

Small in diameter, the FG-ECX sense cable is light, flexible and of an easily identifiable dark blue colour and yellow colour on male connector tip. Its helical jacket construction, compression connected on an extruded central core, reduces the risk of contamination and false alarms. It is made from the highest quality materials which are abrasive resistant in hostile environments.

## Technical Data

Compatibility	Alarm units: FG-ALS8, FG-ALS4; FG-A
Maximum Rated Temperature	85°C
Weight	25g per metre (without connector)
Sense Cable Diameter	7.5 mm with jacket (without connector)
Liquid Quantity to Active Alarm	50-100mm on the sense cable
FG-ECX Colour	Light blue


## Product Diagram



FG-ECX Sense Cable Male Connector Tip



FG-ECX Sense Cable Female Connector Tip



## Identification Codes

FG-ECX15	Analog water sense cable in 15m length with connectors, LSZH
FG-ECX7	Analog water sense cable in 7m length with connectors, LSZH
FG-ECX3	Analog water sense cable in 3m length with connectors, LSZH
<b>Accessories:</b>	
FG-CLC	Leader cable in 3.5 metres length
FG-TMX	Modular end termination plug (for ECX, ACX sense cables)
FG-NC 1, 3, 7, 15, 30	«TTK Bus 8723» Neutral Cable 30m With Connectors
CF-EC100	100 hold-down clips with cold adhesive glue
ES-EC	40 signal tags

## Certificate



This brochure has been carefully prepared to ensure technical accuracy but is only intended for promotional use. TTK cannot guarantee that the information contained herein contains no errors or omissions, and hence does not accept responsibility related to the use of its equipment. TTK maintain its obligations set forth in the Standard Terms and Conditions of Sale and will not, under any circumstances, assume liability for any incidental damages, indirect or consequential, arising from the sale, resale, use or misuse of this project. The purchaser(s) accept their responsibility as the sole judge(s) of the adaptability of the product for the intended use. FG-NET, FG-SYS and TOPSurveillance are trademarks of TTK S.A.S. © TTK 2020