



® Knowledge Beyond Measure.

AeroTrak[®] Remote Particle Counter

Model 7110



The TSI[®] AeroTrak 7110 Portable Particle Counter offers an accurate measurement of particles down to 0.100µm

The accuracy of this instrument is made possible utilizing a patented HeNe laser technology with an enhanced signal-to-noise ratio. This instrument is designed for clean room monitoring, process tool monitoring and filter test applications. And, since the particle counter is used with an external vacuum source, there is significant flexibility in placing and configuring systems.

Particle count data can be easily and continuously transferred to a facility monitoring system, like TSI's FMS for secure data capture and analysis. Specifically, when coupled with FMS, you have a powerful productivity tool with features like Statistical Process Control. These particle counters can also store up to 2,000 sample records, providing data redundancy. The Model 7110 complies with all the stringent requirements set forth in ISO 21501-4. It is calibrated with NIST traceable PSL spheres using TSI's world-class Classifier and Condensation Particle Counters, the recognized standard for particle measurements. Backed by a two-year product workmanship and material warranty and four-year laser warranty as well as the TSI[®] commitment for superior service and support, these remote particle counters are most accurate, high flow, high sensitivity particle counting products on the market today.

Features and Benefits

- Accurately measures particles at 0.100 µm
- 0.100 to 10.0 µm size range
- Up to eight channels of simultaneous data
- 1.0 CFM (28.3 L/min) flow rate
- Complies with all requirements of ISO 21501-4
- Utilizes enhanced HeNe laser
- Highly repeatable and reliable measurements/data
- 2000 sample record storage
- Ethernet Modbus TCP, RS-485 Modbus RTU or Pulse
- Easy to read status indicators
- Easily interfaces with facility monitoring systems
- Stainless steel enclosure
- Easily used with external vacuum pump
- Two-year product workmanship and material warranty
- Four-year laser warranty

Specifications

AeroTrak[®] Remote Particle Counter

Model 7110



Size Range	0.100 to 10.0 µm	Dimension (H x W x D)	5.25 in. x 5.0 in. x 17.9 in. (13.4 cm x 12.7 cm x 45.6 cm)
Particle Channel Sizes	7110-05: 0.10,0.15,0.5,0.25,0.3,0.5,1.0,5.0 µm	Weight	11.5 lb (5.23 kg)
Size Resolution	<15% @ 0.2 µm (per ISO 21501-4)	Power	110 to 240 VAC, universal power supply
Counting Efficiency	50% at 0.100 µm' 100% for particles >0.15 µm (per ISO 21501-4 and JIS)	Standards	ISO 21501-4, CE, JIS B9921
Concentration Limit	100,000 particles/ft ³ (3,500,000/m ³) @ 10% coincidence loss	Warranty	Two year product workmanship and material warranty Four year 0.1 µm laser assembly warranty Extended warranties available
Light Source	Enhanced active cavity HeNe laser (4 year warranty)	Operating Range	50° to 95° F(10° to 35° C), 20% to 95% RH non-condensing
Zero Count	<1 count per 5 minutes (per ISO 21501-4 and JIS)	Storage Range	32° to 122° F (0° to 50° C), up to 98% RH non-condensing
Flow Rate	1 CFM (28.3 L/min)	Included Accessories	Printed QuickStart Guide, Online operating manual, barbed inlet and power supply
Vacuum Requirements	External vacuum > 15 in. (38.1 cm) of Hg	Optional Accessories	Isokinetic inlet, isokinetic probe, purge filter, sample tubing, and vacuum tubing
Calibration	NIST traceable using TSI [®] calibration system		
Calibration Frequency	Recommended minimum of once per year		
Sampling Modes	Manual or Automatic		
Communication Mode	Modbus [®] over RS-485, Modbus [®] over Ethernet, 4-ch CEMS pulse, serial RS-232		
Data Storage	2,000 sample records		
Status Indicators	Power, Service, Sample and Flow		
Alarm Output	Dry contacts, closed when alarm is engaged		
Software	Compatible with FMS 5		
External Surface	Stainless steel		

Specifications are subjected to change without notice.

AeroTrak, TSI and TSI logo are registered trademarks of TSI incorporated in the United States and may be protected under other country's trademark registrations.

Modbus is a registered trademark of Modicon.Inc