


PRODUCT-DETAILS

# AX09-30-01-86

## AX09-30-01-86 400-415V50Hz/415V-440V60Hz

### Contactors



#### General Information

|                       |   |
|-----------------------|---|
| Extended Product Type | AX09-30-01-86   |
| Product ID            | 1SBL901074R8601   |
| EAN                   | 3471522392862   |
| Catalog Description   | AX09-30-01-86 400-415V50Hz/415V-440V60Hz Contactor  |
| Long Description      | AX09...AX25 contactors are mainly used for controlling 3-phase motors and power circuits up to 690 V AC. These contactors are of the block type design with: – 3 main poles and 1 built-in auxiliary contact – control circuit: AC operated – add-on auxiliary contact blocks for front or side mounting and a wide range of accessories. |

#### Classifications

|                            |  |
|----------------------------|--|
| Object Classification Code | Q  |
| ETIM 6                     | EC000066 - Power contactor, AC switching |
| ETIM 7                     | EC000066 - Power contactor, AC switching |
| UNSPSC                     | 39121529                                 |

#### Container Information

|                         |         |
|-------------------------|---------|
| Package Level 1 Units   | 1 piece |
| Package Level 1 Width   | 48 mm   |
| Package Level 1 Depth / | 78 mm   |

## Length

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Height         | 79 mm         |
| Package Level 1 Gross Weight   | 0.34 kg       |
| Package Level 1 EAN            | 3471522392862 |
| Package Level 2 Units          | 30 piece      |
| Package Level 2 Width          | 240 mm        |
| Package Level 2 Depth / Length | 295 mm        |
| Package Level 2 Height         | 145 mm        |
| Package Level 2 Gross Weight   | 10.2 kg       |

---

**Certificates and Declarations (Document Number)**

|                                |                 |
|--------------------------------|-----------------|
| CB Certificate                 | 9AKK107492A7072 |
| CCC Certificate                | 9AKK107492A7089 |
| CCS Certificate                | 9AKK107492A7096 |
| Declaration of Conformity - CE | 1SBD250011U1000 |
| Instructions and Manuals       | 9AKK107492A7057 |
| RoHS Information               | 1SBD251301E1000 |

---

**Technical UL/CSA**

|                              |  |
|------------------------------|--|
| General Use Rating<br>UL/CSA | (600 V AC) 21 A  |
| Horsepower Rating<br>UL/CSA  | (120 V AC) Single Phase 1/2 Hp<br>(240 V AC) Single Phase 1.5 Hp<br>(200 ... 208 V AC) Three Phase 2 Hp<br>(220 ... 240 V AC) Three Phase 2 Hp<br>(440 ... 480 V AC) Three Phase 5 Hp<br>(550 ... 600 V AC) Three Phase 7.5 Hp |
| Tightening Torque<br>UL/CSA  | Auxiliary Circuit 9 in-lb<br>Control Circuit 9 in-lb<br>Main Circuit 9 in-lb   |

---

**Environmental**

|  |  |
|--|--|
| Ambient Air Temperature                | Close to Contactor for Storage -60 ... +80 °C<br>Close to Contactor Fitted with Thermal O/L Relay -25 ... +55 °C<br>Close to Contactor without Thermal O/L Relay -40 ... +70 °C<br>Near Contactor for Operation in Free Air -40 ... +70 °C |
| Climatic Withstand                     | acc. to IEC 60068-2-30 and 60068-2-11 - UTE C 63-100 specification II  |
| Maximum Operating Altitude Permissible | 3000 m   |
| RoHS Status                            | Following EU Directive 2002/95/EC August 18, 2005 and amendment  |

---

**Technical**

|                               |   |
|-------------------------------|---|
| Number of Main Contacts<br>NO | 3 |
| Number of Main Contacts       | 0 |

NC

|  |  |
|--|--|
| Number of Auxiliary Contacts NO                    | 0  |
| Number of Auxiliary Contacts NC                    | 1  |
| Rated Operational Voltage                          | Auxiliary Circuit 690 V<br>Main Circuit 690 V  |
| Rated Frequency (f)                                | Auxiliary Circuit 50 / 60 Hz<br>Main Circuit 50 / 60 Hz  |
| Conventional Free-air Thermal Current ( $I_{th}$ ) | acc. to IEC 60947-4-1, Open Contactors $q = 40\text{ °C}$ 24 A<br>acc. to IEC 60947-5-1, $q = 40\text{ °C}$ 16 A   |
| Rated Operational Current AC-1 ( $I_e$ )           | (690 V) $40\text{ °C}$ 22 A<br>(690 V) $70\text{ °C}$ 18 A<br>(220 / 240 V) $55\text{ °C}$ 22 A  |
| Rated Operational Current AC-3 ( $I_e$ )           | (220 / 230 / 240 V) $55\text{ °C}$ 9 A<br>(380 / 400 V) $55\text{ °C}$ 9 A<br>(415 V) $55\text{ °C}$ 9 A<br>(440 V) $55\text{ °C}$ 9 A<br>(500 V) $55\text{ °C}$ 9 A<br>(690 V) $55\text{ °C}$ 7 A   |
| Rated Operational Power AC-3 ( $P_e$ )             | (220 / 230 / 240 V) 2.2 kW<br>(380 / 400 V) 4 kW<br>(415 V) 4 kW<br>(440 V) 4 kW<br>(500 V) 5.5 kW<br>(690 V) 5.5 kW   |
| Rated Operational Current AC-15 ( $I_e$ )          | (220 / 240 V) 4 A<br>(24 / 127 V) 6 A<br>(400 / 440 V) 2 A<br>(500 V) 2 A<br>(690 V) 2 A<br>(380 / 440 V) 3 A  |
| Rated Short-time Withstand Current ( $I_{cw}$ )    | at $40\text{ °C}$ Ambient Temp, in Free Air, from a Cold State 10 s 100 A<br>at $40\text{ °C}$ Ambient Temp, in Free Air, from a Cold State 15 min 26 A<br>at $40\text{ °C}$ Ambient Temp, in Free Air, from a Cold State 1 min 50 A<br>at $40\text{ °C}$ Ambient Temp, in Free Air, from a Cold State 1 s 250 A<br>at $40\text{ °C}$ Ambient Temp, in Free Air, from a Cold State 30 s 60 A<br>for 0.1 s 140 A<br>for 1 s 100 A |
| Maximum Breaking Capacity                          | $\cos\phi=0.45$ ( $\cos\phi=0.35$ for $I_e > 100$ A) at 440 V 250 A<br>$\cos\phi=0.45$ ( $\cos\phi=0.35$ for $I_e > 100$ A) at 690 V 90 A  |
| Maximum Electrical Switching Frequency             | AC-1 600 cycles per hour<br>AC-15 1200 cycles per hour<br>AC-3 1200 cycles per hour<br>DC-13 900 cycles per hour   |
| Rated Operational Current DC-13 ( $I_e$ )          | (110 V) 1.1 A / 121 W<br>(220 V) 0.55 A / 121 W<br>(400 V) 2.8 A / 134 W<br>(500 V) 2 A / 144 W<br>(125 V) 1.1 A / 138 W<br>(24 V) 6 A / 144 W<br>(250 V) 0.55 A / 138 W   |
| Rated Insulation Voltage ( $U_i$ )                 | acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 690 V   |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )      | 6 kV   |
| Maximum Mechanical Switching Frequency             | 3600 cycles per hour   |
| Rated Control Circuit Voltage ( $U_c$ )            | 50 Hz 400 ... 415 V<br>60 Hz 415 ... 440 V   |
| Operate Time                                       | Between Coil De-energization and NC Contact Closing 9 ... 16 ms  |

Between Coil De-energization and NO Contact Opening 4 ... 11 ms  
 Between Coil Energization and NC Contact Opening 7 ... 21 ms  
 Between Coil Energization and NO Contact Closing 10 ... 26 ms

Degree of Protection acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20  
 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20  
 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20

Terminal Type Screw Terminals

---

## Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 44 mm    |
| Product Net Depth / Length | 74 mm    |
| Product Net Height         | 74 mm    |
| Product Net Weight         | 0.326 kg |

---

## Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | No              |
| Instructions and Manuals          | 9AKK107492A7057 |

---

## Ordering

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85364900 |

---

## Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

