

PRODUCT-DETAILS

OT1600E04P

OT1600E04P SWITCH-DISCONNECTOR



General Information

| | |
|-----------------------|--|
| Extended Product Type | OT1600E04P |
| Product ID | 1SCA022860R6740 |
| EAN | 6417019309385 |
| Catalog Description | OT1600E04P SWITCH-DISCONNECTOR |
| Long Description | 4-pole, front operated, base mounted switch-diconnector with black IP65 handle and shaft, terminal bolt kit included |

Popular Downloads

| | |
|-----------------------------------|---|
| Data Sheet, Technical Information | 1SCC301020C0201 |
| Instructions and Manuals | 1SCC301047M0213 |
| Mechanical Drawings | 1SCC301504F0001 1SCC301503F0001 OT1600E04.igs |

Dimensions

| | |
|---------------------|----------|
| Product Net Width | 414.5 mm |
| Product Net Height | 372 mm |
| Product Net Depth / | 167 mm |

| | |
|--------------------|---------|
| Length | |
| Product Net Weight | 22.3 kg |

Technical

| | |
|---|---|
| Rated Operational Current AC-21A (I_e) | (380 ... 415 V) 1600 A (500 V) 1600 A (690 V) 1600 A (1000 V) 1600 A |
| Rated Operational Current AC-22A (I_e) | (380 ... 415 V) 1600 A (500 V) 1600 A (690 V) 1600 A |
| Rated Operational Current AC-23A (I_e) | (380 ... 415 V) 1250 A (500 V) 1250 A (690 V) 1250 A |
| Rated Operational Power AC-23A (P_e) | (400 ... 415 V) 710 kW (500 V) 900 kW (690 V) 1200 kW |
| Conventional Free-air Thermal Current (I_{th}) | q = 40 °C 1600 A |
| Conventional Thermal Current (I_{the}) | Fully Enclosed 1600 A |
| Rated Impulse Withstand Voltage (U_{imp}) | 12 kV |
| Rated Insulation Voltage (U_i) | acc. to IEC/EN 60664-1 1000 V |
| Rated Operational Voltage | Main Circuit 1000 V |
| Rated Short-Circuit Making Capacity (I_{cm}) | (690 V) 92 kA |
| Rated Short-time Withstand Current (I_{cw}) | for 1 s 50 kA |
| Power Loss | at Rated Operating Conditions per Pole 48 W |
| Pollution Degree | 3 |
| Handle Color | Black |
| Handle Type | Handle and shaft included |
| Fourth Pole Position | Right Side |
| Fourth Pole Type | Switched - Simultaneous Function |
| Switches Operating Mechanism | Mechanism at the End of the Switch 04 (Left Side) |
| Distance Between Phases | Standard |
| Position of Line Terminals | Top In - Bottom Out Bottom In - Top Out |
| Operating Mode | Front operated |
| Standards | IEC 60947-3 |
| Special Functions | No |
| Mounting Type | Base mounting |
| Number of Poles | 4 |
| Degree of Protection | Front IP00 |
| Terminal Type | Lug terminals |
| Terminal Width | 50 mm |
| Tightening Torque | acc. IEC 60947-1 50...75 N·m |
| Mechanical Durability | 6000 |

Environmental

| | |
|---------------------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
| Environmental Information | 1SCC301149D0202 |

Certificates and Declarations (Document Number)

| | |
|-----------------------------------|-----------------|
| Declaration of Conformity - CE | 1SCC301155D2704 |
| DNV GL Certificate | 1SCC301184D0203 |
| Environmental Information | 1SCC301149D0202 |
| Instructions and Manuals | 1SCC301047M0213 |
| RoHS Information | 1SCC301149D0203 |

Container Information

| | |
|-----------------------------------|---------------|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 400 mm |
| Package Level 1 Depth / Length | 435 mm |
| Package Level 1 Height | 170 mm |
| Package Level 1 Gross Weight | 23.3 kg |
| Package Level 1 EAN | 6417019309385 |

Classifications

| | |
|----------------------------|--|
| Object Classification Code | Q |
| ETIM 5 | EC000216 - Switch disconnecter |
| ETIM 6 | EC000216 - Switch disconnecter |
| ETIM 7 | EC000216 - Switch disconnecter |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

