

PRODUCT-DETAILS

OT250E04CP

OT250E04CP CHANGE-OVER SWITCH



General Information	
Extended Product Type	OT250E04CP
Product ID	1SCA022775R4640
EAN	6417019252384
Catalog Description	OT250E04CP CHANGE-OVER SWITCH
Long Description	Including a black plastic IP65 I-0-II pistol type handle (see the table below), shaft and bolt set for the cable connection. Handle padlockable in the 0-position, door interlock in the I- and lipositions and when padlocked.

Popular Downloads	
Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC301040M0002

Dimensions	
Product Net Width	205 mm
Product Net Height	150 mm
Product Net Depth / Length	160 mm
Product Net Weight	3.83 kg
	8.44 lb

Technical	
Rated Operational	(380 415 V) 250 A
Current AC-21A (I _e)	(500 V) 250 A
	(690 V) 250 A
Rated Operational Current AC-22A (I _e)	(380 415 V) 250 A (500 V) 250 A
Current AC-22A (16)	(690 V) 250 A
Rated Operational	(380 415 V) 250 A
Current AC-23A (I _e)	(500 V) 250 A
	(690 V) 250 A
Rated Operational	(380 415 V) 250 A
Current AC-31B (I _e)	(300 415 \\) 350 A
Rated Operational Current AC-33B (I _e)	(380 415 V) 250 A
Rated Operational Power	(380 415 V) 140 kW
AC-23A (P _e)	(500 V) 170 kW
	(690 V) 250 kW
Conventional Free-air	q = 40 °C 250 A
Thermal Current (I _{th})	
Conventional Thermal Current (I _{the})	Fully Enclosed 250 A
Rated Impulse	12 kV
Withstand Voltage (U _{imp}	
)	
Rated Insulation Voltage	1000 V
(U _i)	10001
Rated Operational Voltage	1000 V
Rated Short-time	for 1 s 8 kiloampere rms
Withstand Current (I _{cw})	·
Power Loss	6.5 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating	Mechanism at the End of the Switch
Mechanism	04 (Left Side)
Distance Between Phases	Standard
Position of Line	Top In - Bottom Out, Bottom In - Top Out
Terminals	10p III - Bottoiii Out, Bottoiii III - 10p Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	4
Degree of Protection	Front IP20
Terminal Width	20 mm
Tightening Torque	acc. IEC 60947-1 15 22 N⋅m

Environmental

Environmental 1SCC303050D0201 Information

Certificates and Declarations (Document Number)
--	-----------------	---

Declaration of	1SCC303003D0202
Conformity - CE	
Environmental	1SCC303050D0201
Information	
Instructions and	1SCC301040M0002

Manuals

RoHS Information	1SCC301149D0202

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	186 mm 7.32 in
Package Level 1 Depth / Length	300 mm 11.81 in
Package Level 1 Height	185 mm 7.28 in
Package Level 1 Gross Weight	4.1 kg
Package Level 1 EAN	6417019252384

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Manual\ Change-over\ Switches$

