

(380 ... 415 V) 3200 A

Handle and shaft included

(500 V) 3200 A

q = 40 °C 3200 A

PRODUCT-DETAILS


Technical

Rated Operational

Current AC-21B (I_e)

 $\frac{\text{Conventional Free-air}}{\text{Thermal Current (I_{th})}} \\ \\ \overline{\text{Handle Type}}$

OT3200E04CP OT3200E04CP



Extended Product Type	OT3200E04CF
Product ID	1SCA129158R100:
EAN	6417019588568
Catalog Description	OT3200E04CF
Long Description	Manually operated trasfer switch, handle and shaft need to be ordered separately
Popular Downloads	1SCC340009C020:
Dara Sheet Technical	
Data Sheet, Technical Information	

Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism at the End of the Switch 04 (Left Side)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	4

Container Information		
Package Level 1 Width	590 mm	
	23.23 in	
Package Level 1 Depth /	790 mm	
Length	31.1 in	
Package Level 1 Height	510 mm	
	20.08 in	
Package Level 1 Gross	108.6 kg	
Weight	239.42 lb	
Package Level 1 EAN	6417019588568	

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Manual\ Change-over\ Switches$

