

PRODUCT-DETAILS

## **OT80F4C**

## OT80F4C CHANGE-OVER SWITCH



General Information	
Extended Product Type	OT80F4C
Product ID	1SCA105418R1001
EAN	6417019393537
Catalog Description	OT80F4C CHANGE-OVER SWITCH
Long Description	Handle and shaft has to be ordered separately

Popular Downloads	
Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303008M0203

Dimensions	
Product Net Width	140 mm
Product Net Height	92 mm
Product Net Depth / Length	85 mm
Product Net Weight	0.7 kg

## **Technical**

(380 415 V) 80 A	Rated Operational
(500 V) 80 A	Current AC-21A (I <sub>e</sub> )
(690 V) 80 A	
(380 415 V) 80 A	Rated Operational
(500 V) 80 A	Current AC-22A (I <sub>e</sub> )
(690 V) 80 A	
(380 415 V) 75 A (500 V) 58 A	Rated Operational Current AC-23A (I <sub>e</sub> )
(690 V) 20 A	Culture 25A (ig)
(380 415 V) 37 kW	Rated Operational Power
(500 V) 37 kW	AC-23A (P <sub>e</sub> )
(690 V) 18.5 kW	
q = 40 °C 80 A	Conventional Free-air
	Thermal Current (Ith)
Fully Enclosed 80 A	Conventional Thermal
	Current (I <sub>the</sub> )
8 kV	Rated Impulse
	Withstand Voltage (U <sub>imp</sub> )
750 V	Rated Insulation Voltage
130 V	(U <sub>i</sub> )
750 V	Rated Operational
	Voltage
for 1 s 1.5 kiloampere rms	Rated Short-time
·	Withstand Current (I <sub>cw</sub> )
4.5 W	Power Loss
3	Pollution Degree
Black	Handle Color
Handle and shaft not included	Handle Type
Right Side	Fourth Pole Position
Switched - Simultaneous Function	Fourth Pole Type
Mechanism on Top of the Switch	Switches Operating
	Mechanism
Standard	Distance Between
	Phases
Top In - Bottom Out, Bottom In - Top Out	Position of Line
	Terminals
Front operated	Operating Mode
·	Mounting Type
Base mounting	
Base mounting	Number of Poles

Technical UL/CSA	
Horsepower Rating	(acc. to UL 200 V) 20 Hp
UL/CSA	(acc. to UL 208 V) 20 Hp
	(acc. to UL 240 V) 20 Hp
	(acc. to UL 480 V) 40 Hp
	(acc. to UL 600 V) 40 Hp
Ampere Rating UL/CSA	80 A

Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	1SCC303020D0201
Instructions and Manuals	1SCC303008M0203
RoHS Information	1SCC301183D0201

OT80F4C

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	102 mm
Package Level 1 Depth / Length	205 mm
Package Level 1 Height	103 mm
Package Level 1 Gross Weight	0.76 kg
Package Level 1 EAN	6417019393537

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Manual\ Change-over\ Switches$ 

