

PRODUCT-DETAILS

316BC6W

Ind. P&S#316BC6W



General Information

Extended Product Type	316BC6W
Product ID	2CMA102175R1000
EAN	7392696021753
Catalog Description	Ind. P&S#316BC6W
Long Description	4x16A / IP 67 - Connector Clock Position Of Grounding Contact 6 hour Color code Red

Ordering

EAN	7392696021753
Country of Origin	Turkey (TR)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	89 mm
Product Net Height	89 mm
Product Net Length	143 mm
Product Net Depth / Length	143 mm
Product Net Weight	0.248 kg

Container Information

Package Level 1 Width	150 mm
Package Level 1 Depth / Length	280 mm
Package Level 1 Height	225 mm
Package Level 1 Gross Weight	2.663 kg
Package Level 1 EAN	7392696036559
Package Level 1 Units	box 10 piece

Technical UL/CSA

Ampere Rating UL/CSA	16 A
----------------------	------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Declaration	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Cable Cross-Section	1 ... 2.5 mm ²
Cable Entry Position	Anti-kink sleeve
Color	Red
Connection Type	Screw Clamp
Degree of Protection	IP67
Enclosure Material	Plastic (PA)
Frequency (f)	50 Hz 60 Hz
Function	Connector
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#316BC6W
Material	Plastic
Number of Poles	4
Order Multiple	10 piece
Product Main Type	BC
Product Name	Connector
Protection Type	Watertight
Rated Current (I _n)	16 A
Rated Voltage (U _r)	380 ... 415 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440509
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Basic & Safe

