

PRODUCT-DETAILS

316BP6W

Ind. P&S#316BP6W



General Information

Extended Product Type	316BP6W
Product ID	2CMA102174R1000
EAN	7392696021746
Catalog Description	Ind. P&S#316BP6W
Long Description	4x16A / IP 67 - Plug Clock Position Of Grounding Contact 6 hour Color code Red

Ordering

EAN	7392696021746
Country of Origin	Turkey (TR)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	81 mm
Product Net Height	81 mm
Product Net Length	129 mm
Product Net Depth / Length	129 mm
Product Net Weight	0.196 kg

Container Information

Package Level 1 Width	150 mm
Package Level 1 Depth / Length	280 mm
Package Level 1 Height	225 mm
Package Level 1 Gross Weight	2.143 kg
Package Level 1 EAN	7392696036542
Package Level 1 Units	box 10 piece

Technical UL/CSA

Ampere Rating UL/CSA	16 A
----------------------	------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Declaration	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1025779
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Cable Cross-Section	1 ... 2.5 mm ²
Cable Entry Position	Anti-kink sleeve
Color	Red
Connection Type	Screw Clamp
Degree of Protection	IP67
Enclosure Material	Plastic (PA)
Frequency (f)	50 Hz 60 Hz
Function	Plug
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#316BP6W
Material	Plastic
Number of Poles	4
Order Multiple	10 piece
Product Main Type	BP
Product Name	Plug
Protection Type	Watertight
Rated Current (I _n)	16 A
Rated Voltage (U _r)	380 ... 415 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440509
--------	----------

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Basic & Safe

