

PRODUCT-DETAILS

332BRA6

Ind. P&S#332BRA6



General Information

Extended Product Type	332BRA6
Product ID	2CMA102227R1000
EAN	7392696022279
Catalog Description	Ind. P&S#332BRA6
Long Description	4x32A / IP 44 - Panel Mount Socket Outlet (angled) Clock Position Of Grounding Contact 6 hour Color code Red

Ordering

EAN	7392696022279
Country of Origin	Turkey (TR)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	83 mm
Product Net Height	98 mm
Product Net Length	97 mm
Product Net Depth / Length	97 mm
Product Net Weight	0.219 kg

Container Information

Package Level 1 Width	190 mm
Package Level 1 Depth / Length	265 mm
Package Level 1 Height	230 mm
Package Level 1 Gross Weight	2.531 kg
Package Level 1 EAN	7392696037044
Package Level 1 Units	box 10 piece

Technical UL/CSA

Ampere Rating UL/CSA	32 A
----------------------	------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Declaration	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Cable Cross-Section	2.5 ... 6 mm ²
Color	Red
Connection Type	Screw Clamp
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Outlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#332BRA6
Material	Plastic
Mounting Holes	76x70
Mounting Type	Angled
Number of Poles	4
Order Multiple	10 piece
Product Main Type	BRA
Product Name	Panel mounted socket
Protection Type	Watertight
Rated Current (I _n)	32 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U _r)	380 ... 415 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 3002 - Carmine Red

Classifications

eClass	27440504
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Basic & Safe

