

PRODUCT-DETAILS

432BC6W

Ind. P&S#432BC6W



General Information

Extended Product Type	432BC6W
Product ID	2CMA102254R1000
EAN	7392696022545
Catalog Description	Ind. P&S#432BC6W
Long Description	Industrial Connectors, 3P+N+E, 32A, 200/346 ... 240/415 V Clock Position Of Grounding Contact 6 hour Color code Red

Ordering

EAN	7392696022545
Country of Origin	Turkey (TR)
Minimum Order Quantity	5 piece

Dimensions

Product Net Width	109 mm
Product Net Height	109 mm
Product Net Length	173 mm
Product Net Depth / Length	173 mm

Product Net Weight	0.324 kg
--------------------	----------

Container Information

Package Level 1 Width	150 mm
Package Level 1 Depth / Length	280 mm
Package Level 1 Height	225 mm
Package Level 1 Gross Weight	1.803 kg
Package Level 1 EAN	7392696037303
Package Level 1 Units	box 5 piece

Technical UL/CSA

Ampere Rating UL/CSA	32 A
----------------------	------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Declaration	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Cable Cross-Section	2.5 ... 6 mm ²
Cable Entry Position	Anti-kink sleeve
Color	Red
Connection Type	Screw Clamp
Degree of Protection	IP67
Enclosure Material	Plastic (PA)
Frequency (f)	50 Hz 60 Hz
Function	Connector
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#432BC6W
Material	Plastic
Number of Poles	5
Order Multiple	5 piece
Product Main Type	BC
Product Name	Connector
Protection Type	Watertight
Rated Current (I _n)	32 A

200/346 ... 240/415 V

Rated Voltage (U_r)

Standards

IEC 60309-1, -2

Suitable for Product Class

IEC Industrial Plugs and Sockets

Instructions and Manuals

2CMC700014C0016

RAL Number

RAL 7012 - Basalt Grey

Classifications

eClass

27440509

UNSPSC

39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Basic & Safe

