

PRODUCT-DETAILS

463C6W

Ind. P&S#463C6W



General Information

| | |
|-----------------------|---|
| Extended Product Type | 463C6W |
| Product ID | 2CMA166906R1000 |
| EAN | 7392696669061 |
| Catalog Description | Ind. P&S#463C6W |
| Long Description | Connector, earthing sleeve position 6h, rated current 63A, IP67 watertight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red |

Ordering

| | |
|------------------------|---------------------|
| E-Number (Sweden) | E2416418 |
| E-Number (Finland) | 2421743 |
| E-Number (Norway) | 1563883 |
| EAN | 7392696669061 |
| Country of Origin | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece |

Dimensions

| | |
|--------------------|--------|
| Product Net Width | 108 mm |
| Product Net Height | 112 mm |

| | |
|----------------------------|-----------------|
| Product Net Length | 286 mm |
| Product Net Depth / Length | 286 mm |
| Product Net Weight | 0.88 kg |
| Mechanical Drawings | 9AKK107492A4188 |

Container Information

| | |
|--------------------------------|--------------|
| Package Level 1 Width | 138 mm |
| Package Level 1 Depth / Length | 158 mm |
| Package Level 1 Height | 345 mm |
| Package Level 1 Gross Weight | 0.88 kg |
| Package Level 1 EAN | 739269669061 |
| Package Level 1 Units | box 1 piece |
| Package Level 2 Units | 66 piece |

Technical UL/CSA

| | |
|----------------------|------|
| Ampere Rating UL/CSA | 63 A |
|----------------------|------|

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Declaration | 2CMC700005D0001 |
| Environmental Information | 2CMC000056M0000 |
| RoHS Information | 2CMC700005D0001 |
| SEMKO Certificate | 1614200 |
| REACH Declaration | 2CMC700005D0001 |

Additional Information

| | |
|------------------------|---|
| Additional Information | 3P+N+E |
| Ambient Temperature | -25 ... 40 °C |
| Cable Cross-Section | 4 ... 16 mm ² |
| Cable Entry Position | Cable entry, compression gland, internal and external cable clamp |
| Color | Red |
| Connection Type | Screw Clamp |
| Degree of Protection | IP67 IP69 |
| Enclosure Material | Thermoplastic polyester (PBT) |
| Frequency (f) | 50 Hz 60 Hz |
| Function | Connector |
| Housing Material | Thermoplastic (PBT) |
| Invoice Description | Ind. P&S#463C6W |

| | |
|----------------------------|----------------------------------|
| Material | Plastic |
| Number of Poles | 5 |
| Order Multiple | 1 piece |
| Product Main Type | TC |
| Product Name | Industrial Connector |
| Protection Type | Watertight |
| Rated Current (I_n) | 63 A |
| Rated Voltage (U_r) | 200/346 ... 240/415 V |
| Recommended Screw Driver | PH2 |
| RoHS Date | L23 |
| Standards | IEC 60309-1, -2 |
| Suitable For | Connectors |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals | 2CMC000038M0001 |
| Installation Manual | 2CMC000038M0001 |
| RAL Number | RAL 7001 - Silver Grey |

Classifications

| | |
|--------|----------|
| eClass | 27440509 |
| UNSPSC | 39120000 |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Connectors

