

PRODUCT-DETAILS

B21 112-100

Active Energy Class ±1% (or B for MID meters).;



| O | 1 . 6 |
|---------|-------------|
| General | Information |

| Extended Product Type | B21 112-100 |
|-----------------------|---|
| Product ID | 2CMA100150R1000 |
| ABB Type Designation | B21 112-100 |
| EAN | 7392696001502 |
| Catalog Description | Active Energy Class ±1% (or B for MID meters).; |

Long Description

Advanced compact DIN-rail meter with an easy to read back lighted display. The meter is intended for use in the commercial or residential buildings etc. The meter can be used in 3 or 4 wire systems. The meter has several instrumentation values, 25 possible alarms and event logs. Single phase direct connected for active energy. One output for pulses or alarm etc. RS-485 communication over Modbus RTU or EQ Bus. Accuracy class 1.0 (or B for MID meters). The meters is IEC approved + MID approved and verified.

Ordering

| E-Number (Sweden) | 0900030 |
|------------------------|---------------|
| EAN | 7392696001502 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 90283011 |

Dimensions

| Product Net Width | 35 mm |
|----------------------------|---------|
| Product Net Height | 26.5 mm |
| Product Net Depth / Length | 65 mm |
| Product Net Weight | 0.15 kg |

| Container Information | |
|---------------------------------|---------------|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 70 mm |
| Package Level 1 Height | 50 mm |
| Package Level 1 Depth / Length | 102 mm |
| Package Level 1 Gross Weight | 0.20 kg |
| Package Level 1 EAN | 7392696001502 |

| Environmental | |
|-------------------------|---|
| Ambient Air Temperature | Operation -40 +70 °C |
| RoHS Status | Following EU Directive 2002/95/EC August 18, 2005 and amendment |

| Additional Information | |
|-------------------------------------|--|
| Accuracy | Active Energy Class ±1% (or B for MID meters). |
| Communication Interface | Modbus |
| Communication | MODBUS RTU |
| Connecting Capacity Main Circuit | 1 25 mm² |
| Current Rating | 65 A |
| Degree of Protection | IP20 |
| Enclosure Material | Plastic |
| Frequency (f) | 50/60 Hz |
| Function | Electricity meter |
| Meter Type | Direct connected |
| Mounting Type | DIN rail |
| Number of Phases | 1 |
| Product Main Type | B21 |
| Product Name | Electricity Meter |
| Rated Current (I _n) | 65 A |
| Rated Voltage (U _r) | 220 240 V |
| RoHS Date | 2012-36 |
| Standards | EN 50470-3 |
| Sub-Function | Steel |

Certificates and Declarations (Document Number)

Data Sheet, Technical 2CMC485004M0201

Information

| Declaration of Conformity - CE | 2CMC485001D0001 |
|--------------------------------|-----------------|
| Environmental Information | 2CMC485004D0001 |
| Instructions and Manuals | 2CMC485019M0201 |
| RoHS Information | 2CMC485005 |

| Classifications | |
|----------------------------|--|
| ETIM 4 | EC001506 - Electronic kilowatt-hour meter |
| ETIM 5 | EC001506 - Kilowatt-hour meter |
| ETIM 6 | EC001506 - Kilowatt-hour meter |
| ETIM 7 | EC001506 - Kilowatt-hour meter |
| Object Classification Code | P |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Modular\ DIN\ Rail\ Products \rightarrow Energy\ Efficiency\ Devices \rightarrow Energy\ Meters$

