

PRODUCT-DETAILS

# FA2N/MS 800 4p FHR

# FA2N/MS 800 4p FHR



## General Information

Extended Product Type	FA2N/MS 800 4p FHR
Product ID	1SDA080464R1
EAN	8015644869922
Catalog Description	FA2N/MS 800 4p FHR
Long Description	C.BREAKER SWITCH-DISCONNECTOR FORMULA AIR FA2N/MS 800 FIXED FOUR-POLE WITH TERMINALS REAR HORIZONTAL

## Ordering

EAN	8015644869922
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

## Dimensions

Product Net Width	366 mm
Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	45 kg

## Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	615 mm
Package Level 1 Gross Weight	58 kg
Package Level 1 EAN	8015644869922

## Additional Information

Current Type	AC
Electrical Durability	30 cycles per hour
Mechanical Durability	60 cycles per hour
Neutral Pole Current ([% I <sub>n</sub> ])	100 %
Number of Poles	4
Product Main Type	Formula Air
Product Name	Switch-disconnector
Product Type	Switch-disconnector
Rated Current (I <sub>n</sub> )	800 A
Rated Voltage (U <sub>r</sub> )	690 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	12 kV
Rated Insulation Voltage (U <sub>i</sub> )	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Short-time Withstand Current (I <sub>cw</sub> )	for 1 s 50 kA for 3 s 36 kA
Rated Uninterrupted Current (I <sub>u</sub> )	800 A
Standards	IEC
Sub-type	FA2
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	1SDC200044D0201
Declaration of Conformity - CE	9AAK10103A1376
Environmental Information	Not Available
Instructions and Manuals	1SDH001600R0002

## Classifications

ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## Categories

---

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Formula AIR

