

PRODUCT-DETAILS

XLP1-6BC

XLP1-6BC Fuse Switch Disconnecter



General Information

Extended Product Type	XLP1-6BC
Product ID	1SEP101891R0002
EAN	7025840013730
Catalog Description	XLP1-6BC Fuse Switch Disconnecter
Long Description	XLP1,3-pole,250A, incl. 6 Bridge Clamps

Popular Downloads

Data Sheet, Technical Information	1SEC312012D0201
-----------------------------------	-----------------

Dimensions

Product Net Width	185 mm
Product Net Height	270 mm
Product Net Depth / Length	116 mm
Product Net Weight	1.8 kg

Technical

Rated Operational Current AC-21B (I _e)	(690 V) 200 A
--	---------------

Rated Operational Current AC-22B (I _e)	(500 V) 250 A (800 V) 160 A
Rated Impulse Withstand Voltage (U _{imp})	Main Circuit 8 kV
Rated Operational Voltage	500 V AC 690 V AC 800 V AC
Rated Frequency (f)	Main Circuit 50/60 Hz
Rated Conditional Short-Circuit Current (I _{nc})	(690 V) 50 kiloampere rms
Handle Type	Front cover 3P
Fuse Size	NH1
Fuse System	DIN
Standards	IEC60947-3
Special Functions	Not Included
Mounting Type	Baseplate
Number of Poles	3
Degree of Protection	IP30
Terminal Type	Cable Clamp

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SEP500050P0001
--------------------------------	-----------------

Container Information

Package Level 1 Units	shrink-wrap 1 piece
Package Level 1 Width	185 mm
Package Level 1 Depth / Length	116 mm
Package Level 1 Height	270 mm
Package Level 1 Gross Weight	1.8 kg
Package Level 1 EAN	7025840013730
Package Level 2 EAN	7025840013730

Classifications

Object Classification Code	S
ETIM 4	EC001040 - Fuse switch disconnecter
ETIM 5	EC001040 - Fuse switch disconnecter
ETIM 6	EC001040 - Fuse switch disconnecter
ETIM 7	EC001040 - Fuse switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → EasyLine

