


PRODUCT-DETAILS

CA5X-22E

CA5X-22E Auxiliary contact block



General Information

Extended Product Type	CA5X-22E
Product ID	1SBN019040R1022
EAN	3471522387721
Catalog Description	CA5X-22E Auxiliary contact block
Long Description	CA5X 4-pole Auxiliary Contact Block

Ordering

EAN	3471522387721
Minimum Order Quantity	2 piece
Customs Tariff Number	85030099

Dimensions

Product Net Width	43 mm
Product Net Height	47 mm
Product Net Depth / Length	32.5 mm
Product Net Weight	60 kg

Container Information

Package Level 1 Units	2 piece
-----------------------	---------

Package Level 1 Width	65 mm
Package Level 1 Height	40 mm
Package Level 1 Depth / Length	130 mm
Package Level 1 Gross Weight	0.12 kg
Package Level 1 EAN	3471522387721
Package Level 2 Units	120 piece
Package Level 2 Width	220 mm
Package Level 2 Height	300 mm
Package Level 2 Depth / Length	380 mm
Package Level 2 Gross Weight	7.2 kg

Additional Information

Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-5-1, q = 40 °C 16 A
Maximum Electrical Switching Frequency	AC-15 1200 cycles per hour DC-13 900 cycles per hour
Maximum Mechanical Switching Frequency	3600 cycles per hour
Number of Auxiliary Contacts NC	2
Number of Auxiliary Contacts NO	2
Order Multiple	2 piece
Product Main Type	Accessories for Block Contactors
Product Name	Auxiliary Contact Block
Rated Insulation Voltage (U_i)	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V
Rated Operational Current AC-15 (I_e)	(220 / 240 V) 4 A (24 / 127 V) 6 A (690 V) 2 A (380 / 440 V) 3 A
Rated Operational Current DC-13 (I_e)	(110 V) 0.55 A / 60 W (220 V) 0.30 A / 66 W (400 V) 2.8 A / 134 W (500 V) 1 A / 72 W (125 V) 0.55 A / 69 W (24 V) 6 A / 144 W (250 V) 0.30 A / 75 W
Rated Operational Voltage	Auxiliary Circuit 690 V Main Circuit 690 V
Rated Short-time Withstand Current (I_{cw})	for 0.1 s 140 A for 1 s 100 A
Suitable For	AX50 AX65 AX80 AX95 AX115 AX150
Terminal Type	Screw Terminals

Certificates and Declarations (Document Number)

CCC Certificate	CCC_2014010304725046
Data Sheet, Technical Information	No
Declaration of Conformity - CE	1SBD250013U1000
Instructions and	1SBC101044M9801

Classifications

ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
Object Classification Code	K
UNSPSC	39121500
IDEA Granular Category Code (IGCC)	4743 >> Auxiliary contact block

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors Accessories

