



Product Net Weight	0.03 kg
--------------------	---------

---

## Technical

Rated Operational Voltage	Auxiliary Circuit 12 ... 240 V DC Auxiliary Circuit 12 ... 500 V AC/DC
Rated Frequency (f)	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC
Rated Impulse Withstand Voltage ( $U_{imp}$ )	Auxiliary Circuit 6 kV
Rated Insulation Voltage ( $U_i$ )	690 V
Degree of Protection	IP20
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 1 ... 2.5 mm <sup>2</sup> Flexible 1/2x 1 ... 2.5 mm <sup>2</sup> Rigid 1/2x 1 ... 4 mm <sup>2</sup>
Tightening Torque	Auxiliary Circuit 0.8 ... 1.1 N·m
Wire Stripping Length	Auxiliary Circuit 9 mm
Standards	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Number of Main Contacts NC	0
Number of Main Contacts NO	0
Conventional Free-air Thermal Current ( $I_{th}$ )	Auxiliary Circuit 6 A
Product Name	Auxiliary Contact
Suitable For	B6-30-10 BC6-30-10 B7-30-10 BC7-30-10
Suitable for Product Class	Mini Contactors

---

## Technical UL/CSA

Maximum Operating Voltage UL/CSA	Auxiliary Circuit 600 V AC/DC
Connecting Capacity Auxiliary Circuit UL/CSA	Stranded 1/2x 22-10 AWG
Tightening Torque UL/CSA	Auxiliary Circuit 7 in·lb
Contact Rating UL/CSA	A600

---

## Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +80 °C
Maximum Operating Altitude Permissible	2000 m
Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 15g
Resistance to Vibrations	5g / 5 ... 150 Hz

acc. to IEC 60068-2-6

RoHS Status

Following EU Directive 2011/65/EU

---

### Certificates and Declarations (Document Number)

CB Certificate	1SAA938001-2001
CCC Certificate	1SAA938000-3804
cULus Certificate	cUL_E48139
Declaration of Conformity - CE	1SAD938516-0001
EAC Certificate	1SAA938002-2701
GL Certificate	1SAA938000-0403
RMRS Certificate	1SAA938001-0703
RoHS Information	1SAD938514-0001
UL Certificate	UL_E48139

---

### Container Information

Package Level 1 Width	112 mm
Package Level 1 Depth / Length	142 mm
Package Level 1 Height	62 mm
Package Level 1 Gross Weight	0.365 kg
Package Level 1 EAN	4013614412103
Package Level 1 Units	10 piece

---

### Classifications

Object Classification Code	K
ETIM 4	EC000041 - Auxiliary contact block
ETIM 5	EC000041 - Auxiliary contact block
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
eClass	7.0 27371302
UNSPSC	39121522
E-Number (Sweden)	3210097

---

### Categories

Low Voltage Products and Systems → Control Products → Contactors → Mini Contactors Accessories

