

PRODUCT-DETAILS

CAF6-02K

CAF6-02K Auxiliary Contact



General Information

| | |
|-----------------------|---|
| Extended Product Type | CAF6-02K |
| Product ID | GJL1201330R0009 |
| EAN | 4013614148354 |
| Catalog Description | CAF6-02K Auxiliary Contact |
| Long Description | The CAF6-02K is an auxiliary contact for front mounting with 2 auxiliary contact and screw terminals. |

Ordering

| | |
|------------------------|----------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85365080 |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SBC100173C0201 |
| Instructions and Manuals | 2CDC102005M0101 |
| Instructions and Manuals (Part 2) | 2CDC102005M0101 |
| Dimension Diagram | GJL1200446F0001 |

Dimensions

| | |
|----------------------------|---------|
| Product Net Width | 47.5 mm |
| Product Net Height | 29 mm |
| Product Net Depth / Length | 26.5 mm |
| Product Net Weight | 0.02 kg |

Technical

| | |
|--|---|
| Rated Operational Voltage | Auxiliary Circuit 12 ... 240 V DC Auxiliary Circuit 12 ... 500 V AC/DC |
| Rated Frequency (f) | Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC |
| Rated Impulse Withstand Voltage (U _{imp}) | Auxiliary Circuit 6 kV |
| Rated Insulation Voltage (U _i) | 690 V |
| Degree of Protection | IP20 |
| Connecting Capacity Auxiliary Circuit | Flexible with Ferrule 1/2x 1 ... 2.5 mm ² Flexible 1/2x 1 ... 2.5 mm ² Rigid 1/2x 1 ... 4 mm ² |
| Tightening Torque | Auxiliary Circuit 0.8 ... 1.1 N·m |
| Wire Stripping Length | Auxiliary Circuit 9 mm |
| Standards | IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1 |
| Number of Auxiliary Contacts NO | 0 |
| Number of Auxiliary Contacts NC | 2 |
| Number of Main Contacts NC | 0 |
| Number of Main Contacts NO | 0 |
| Conventional Free-air Thermal Current (I _{th}) | Auxiliary Circuit 6 A |
| Product Name | Auxiliary Contact |
| Suitable For | K6 KC6 |
| Suitable for Product Class | Mini Contactors |

Technical UL/CSA

| | |
|--|-------------------------------|
| Maximum Operating Voltage UL/CSA | Auxiliary Circuit 600 V AC/DC |
| Connecting Capacity Auxiliary Circuit UL/CSA | Stranded 1/2x 22-10 AWG |
| Tightening Torque UL/CSA | Auxiliary Circuit 7 in·lb |
| Contact Rating UL/CSA | A600 |

Environmental

| | |
|--|--|
| Ambient Air Temperature | Operation -25 ... +55 °C Storage -40 ... +80 °C |
| Maximum Operating Altitude Permissible | 2000 m |
| Resistance to Shock acc. | 11 ms Pulse 15g |

to IEC 60068-2-27

| | |
|---|-----------------------------------|
| Resistance to Vibrations acc. to IEC 60068-2-6 | 5g / 5 ... 150 Hz |
| RoHS Status | Following EU Directive 2011/65/EU |

Certificates and Declarations (Document Number)

| | |
|--------------------------------------|-----------------|
| CCC Certificate | 1SAA938000-3804 |
| cULus Certificate | cUL_E48139 |
| Declaration of Conformity - CE | 1SAD938516-0001 |
| EAC Certificate | 1SAA938002-2701 |
| GL Certificate | 1SAA938000-0403 |
| Instructions and Manuals | 2CDC102005M0101 |
| Instructions and Manuals (Part 2) | 2CDC102005M0101 |
| RMRS Certificate | 1SAA938001-0703 |
| RoHS Information | 1SAD938514-0001 |
| UL Certificate | UL_E48139 |

Container Information

| | |
|-----------------------------------|---------------|
| Package Level 1 Width | 115 mm |
| Package Level 1 Depth / Length | 280 mm |
| Package Level 1 Height | 54 mm |
| Package Level 1 Gross Weight | 0.24 kg |
| Package Level 1 EAN | 4013614412301 |
| Package Level 1 Units | 10 piece |

Classifications

| | |
|-------------------------------|------------------------------------|
| Object Classification Code | K |
| ETIM 4 | EC000041 - Auxiliary contact block |
| ETIM 5 | EC000041 - Auxiliary contact block |
| ETIM 6 | EC000041 - Auxiliary contact block |
| ETIM 7 | EC000041 - Auxiliary contact block |
| eClass | 7.0 27371302 |
| UNSPSC | 39121522 |

Categories

Low Voltage Products and Systems → Control Products → Contactors → Mini Contactors Accessories

