

PRODUCT-DETAILS

CAL16-11A

CAL16-11A Auxiliary Contact Block



| General Information | |
|-----------------------|--|
| Extended Product Type | CAL16-11A |
| Product ID | SK829002-A |
| EAN | 7320500002964 |
| Catalog Description | CAL16-11A Auxiliary Contact Block |
| Long Description | 2 pole screw type left side mounted auxilliary contact block, instantaneous N.O. and |

| Ordering | |
|---------------|--|
| 7320500002964 | |
| 1 piece | |
| 85369010 | |
| | |

| Dimensions | |
|----------------------------|---------|
| Product Net Width | 12.5 mm |
| Product Net Height | 68 mm |
| Product Net Depth / Length | 70 mm |
| Product Net Weight | 0.05 kg |

Container Information

| Package Level 1 Units | bag 1 piece |
|---------------------------------|---------------|
| Package Level 1 Width | 100 mm |
| Package Level 1 Height | 18 mm |
| Package Level 1 Depth / Length | 100 mm |
| Package Level 1 Gross Weight | 0.06 kg |
| Package Level 1 EAN | 7320500002964 |

Environmental

| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|
|-------------|-----------------------------------|

| Additional Information | |
|---|--|
| Conventional Free-air Thermal Current (I _{th}) | acc. to IEC 60947-5-1, q = 40 °C 16 A |
| Connecting Terminals (delivered in open position) | M 3.5 (+,-) pozidriv 2 screw with cable clamp |
| Degree of Protection | acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 |
| Minimum Switching Capacity | 0.25 VA/ 12 V / 5 mA |
| Power Loss | at Rated Operating Conditions per Pole 0.2 W |
| Product Main Type | CAL16 |
| Product Name | Auxiliary Contact Block |
| Rated Breaking Capacity acc. to IEC 60947-5-1 | 10 x le AC-15 |
| Rated Frequency (f) | Supply Circuit 50 60 Hz |
| Rated Insulation Voltage (U _i) | acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V |
| Rated Making Capacity acc. to IEC 60947-5-1 | 10 x le AC-15 |
| Rated Operational Current AC-15 (I _e) | (220 / 240 V) 6 A (24 / 127 V) 6 A (380 / 440 V) 4 A (500 V) 1 A (690 V) 1 A |
| Rated Operational Current DC-13 (I _e) | (125 V) 1.8 A (24 V) 6 A (250 V) 0.6 A (48 V) 6 A (72 V) 4 A |
| Rated Short-time Withstand Current (I _{CW}) | for 0.1 s 100 A for 1 s 50 A |
| Replaced Product ID (OLD) | 9262465-525 |
| RoHS Date | 1713 |
| Suitable For | A-line |
| Suitable for Product Class | CONTACTORS |
| Technical Information | AUXILIARY CONTACT |

| Certificates and Declarations (Document Number) | |
|---|-----------------|
| Data Sheet, Technical | 1SBC100122C0202 |
| Information | |
| Declaration of | 2CMT2015-005448 |
| Conformity - CE | |
| Instructions and | 5309660-30 |
| Manuals | |

CAL16-11A 3

RoHS Information 2CMT2016-006025

| Classifications | |
|-------------------------------|--|
| ETIM 4 | EC000041 - Auxiliary contact block |
| ETIM 5 | EC000041 - Auxiliary contact block |
| ETIM 6 | EC000041 - Auxiliary contact block |
| ETIM 7 | EC000041 - Auxiliary contact block |
| Object Classification Code | к |
| UNSPSC | 39121500 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

 $\textbf{Low Voltage Products and Systems} \rightarrow \textbf{Control Products} \rightarrow \textbf{Contactors} \rightarrow \textbf{Block Contactors Accessories}$

