

---

PRODUCT-DETAILS

# NX31E-80

## NX31E-80 220-230V50Hz/230-240V60Hz

### Contactor relay

---

#### General Information

Extended Product Type	NX31E-80
Product ID	1SBH901074R8031
EAN	3471522389800
Catalog Description	NX31E-80 220-230V50Hz/230-240V60Hz Contactor relay
Long Description	NX...contactor relays are used for switching auxiliary circuits and control circuits. These contactor relays are of the block type design with: – 4 poles. Contactor relays have mechanically linked auxiliary contact elements – control circuit: AC operated – add-on auxiliary contact blocks for front or side mounting and a wide range of accessories.

---

#### Classifications

Object Classification Code	K
ETIM 6	EC000196 - Contactor relay
ETIM 7	EC000196 - Contactor relay
UNSPSC	39121500
IDEA Granular Category Code (IGCC)	4755 >> Contactors

---

#### Container Information

Package Level 1 Units	1 piece
-----------------------	---------

Package Level 1 Width	48 mm
Package Level 1 Depth / Length	78 mm
Package Level 1 Height	79 mm
Package Level 1 Gross Weight	0.315 kg
Package Level 1 EAN	3471522389800
Package Level 2 Units	30 piece
Package Level 2 Width	240 mm
Package Level 2 Depth / Length	295 mm
Package Level 2 Height	145 mm
Package Level 2 Gross Weight	9.45 kg

### Certificates and Declarations (Document Number)

CB Certificate	9AKK107492A7071
CCC Certificate	9AKK107492A7095
CCS Certificate	9AKK107492A7097
Declaration of Conformity - CE	1SBD250012U1000
Instructions and Manuals	No
RoHS Information	1SBD251301E1000

### Technical UL/CSA

Tightening Torque UL/CSA	Auxiliary Circuit 9 in-lb Control Circuit 9 in-lb
--------------------------	--

### Environmental

Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 °C Close to Contactor Fitted with Thermal O/L Relay -25 ... +55 °C Close to Contactor without Thermal O/L Relay -40 ... +70 °C Near Contactor for Operation in Free Air -40 ... +70 °C
Climatic Withstand	acc. to IEC 60068-2-30 and 60068-2-11 - UTE C 63-100 specification II
Maximum Operating Altitude Permissible	3000 m
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

### Technical

Number of Auxiliary Contacts NO	3
Number of Auxiliary Contacts NC	1
Rated Operational Voltage	Auxiliary Circuit 690 V Main Circuit 690 V
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz
Conventional Free-air	acc. to IEC 60947-5-1, q = 40 °C 16 A

Thermal Current ( $I_{th}$ )

Rated Operational Current AC-15 ( $I_{\theta}$ )	(220 / 240 V) 4 A (24 / 127 V) 6 A (400 / 440 V) 2 A (500 V) 2 A (690 V) 2 A (380 / 440 V) 3 A
---	---

Rated Short-time Withstand Current ( $I_{cw}$ )	for 0.1 s 140 A for 1 s 100 A
--	----------------------------------

Maximum Electrical Switching Frequency	AC-15 1200 cycles per hour DC-13 900 cycles per hour
---	---

Rated Operational Current DC-13 ( $I_{\theta}$ )	(110 V) 0.55 A / 60 W (220 V) 0.30 A / 66 W (400 V) 2.8 A / 134 W (500 V) 1 A / 72 W (125 V) 0.55 A / 69 W (24 V) 6 A / 144 W (250 V) 0.30 A / 75 W
---	---

Rated Insulation Voltage ( $U_i$ )	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V
---------------------------------------	--

Rated Impulse Withstand Voltage ( $U_{imp}$ )	6 kV
--	------

Maximum Mechanical Switching Frequency	6000 cycles per hour
---	----------------------

Rated Control Circuit Voltage ( $U_c$ )	50 Hz 220 ... 230 V 60 Hz 230 ... 240 V
--	--

Operate Time	Between Coil De-energization and NC Contact Closing 9 ... 16 ms Between Coil De-energization and NO Contact Opening 4 ... 11 ms Between Coil Energization and NC Contact Opening 7 ... 21 ms Between Coil Energization and NO Contact Closing 10 ... 26 ms
--------------	---

Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20
----------------------	--

Terminal Type	Screw Terminals
---------------	-----------------

---

## Dimensions

Product Net Width	44 mm
-------------------	-------

Product Net Depth / Length	74 mm
-------------------------------	-------

Product Net Height	74 mm
--------------------	-------

Product Net Weight	0.315 kg
--------------------	----------

---

## Popular Downloads

Data Sheet, Technical Information	No
--------------------------------------	----

Instructions and Manuals	No
--------------------------	----

---

## Ordering

Minimum Order Quantity	1 piece
------------------------	---------

Customs Tariff Number	85364900
-----------------------	----------

---

## Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors